

To be confirmed.  
Extent of any underbuild  
Gas regime

Gas membrane TBC  
Gas Venting TBC

**Insulslab SFRC Foundation Installation Methodology.**

Described below is a method of construction to utilise the INSULSLAB form of waffle slab foundation in conditions where the foundation is supported at shallow depth directly by the underlying soils. For piled foundations using INSULSLAB similar methods apply.  
Whilst accepting that individual interpretation and innovation may well give rise to alternative methods to suit site specific conditions, it is felt that what is described, will clearly and accurately achieve the end product.  
Severely sloping sites will introduce individual conditions to be addressed which can be readily accounted for by referring to INSULSLAB technical, however for the purposes of this exercise we have assumed a relatively level site.

THIS DRAWING IS COPYRIGHT AND MUST NOT BE REPRODUCED WHOLLY OR IN PART WITHOUT PRIOR PERMISSION.  
© 2012. GHW CONSULTING ENGINEERS LTD. / INSULSLAB SIG

**General Notes.**

1. Insulslab foundation to be placed on minimum 150mm Type 2 granular material to be compacted in accordance with the specification.
2. All works to be undertaken in accordance with the recommendations contained within the geotechnical report and NHBC Standards. Where trees are present, ground conditions may require the placing of an additional hardcore bed under the whole area to overcome the influence of trees/penetrable soils in accordance with the NHBC Standards Chapter 4.2 and 4.5.
3. For depths of sub-base required beneath edge beams refer to sections.
4. The Insulslab pods have a load bearing requirement and are protected by a patent. Online technical data and ordering information can be found on the website [www.insulslab.com](http://www.insulslab.com).
5. Slab to be cured under a spray application of curing / sealing solution, Prematran Pro-Seal or similar.
6. Where ground levels have been adjusted to suit site set-out requirements, it has been assumed that infill / regrade material has been suitably engineered and consolidated in order to achieve a minimum ground bearing capacity of 50kN/m<sup>2</sup>.
7. For all general details and sections see drawing No. 100.
8. For on site setting out of units, orientation / handling and co-ordination, see Architects detail drawings and relevant site setting out drawings by others.
9. For all finished ground levels and slab levels, see Architects / Set-out drawings by others.
10. For setting out of all services, drainage and utilities see Architects and specialists detail drawings.

**Specification for Concrete and Fibres.**

1. The concrete mix shall follow the recommendations as noted in the ArcolorMittal Sheffield Ltd. BBA Certification 12 / 4894 product sheet 2 "ArcolorMittal - Insulslab foundation system for housing applications using SFRC" page 3, Table 1 Concrete Specifications along with the following mix design guide lines. These are to be considered together and neither is to be considered complete without the other.
2. Concrete mix design shall be based on the use of 20mm aggregate. Other aggregate sizes or blends may be used on further review by ArcolorMittal in conjunction with the ready-mix supplier and only formal written confirmation from ArcolorMittal. The proportions will depend on the gradation of the local materials.
3. The concrete grade to be a C30 / 37 - C35 with a maximum water cement ratio of 0.55 using super-plasticiser. All admixtures used should be from the same manufacturer and used as per manufacturers instructions.
4. Permitted cement type shall be Portland cement or blends of up to 20% replacement using GGBS or PFA. This corresponds to the following cement types to BS EN 197-1: CEM I, CEM III/A-S OR CEM III/A-V. Minimum cement quantity to be 320kg/m<sup>3</sup>.
5. The slump shall be between 180 and 230mm (S4 type EN206 / BS8500) at the time of delivery. The addition of water on site is prohibited, except where the additional water is allowable water remaining from the original batch target. Any water added to the concrete shall be recorded on the delivery ticket.
6. The fines content shall be approximately 50% by weight of the total aggregate content. Total fines content shall be 450kg/m<sup>3</sup> fines graded at or below 200µ. Please refer to the required sieve curve analysis for optimum aggregate gradation to be used when investigating the suitability of the given mix.
7. Steel fibres to be HE+1/50. Dosage rate is 50 kg/m<sup>3</sup>.

**NOTE:**  
LAYOUT SHOWN IS INDICATIVE AND SUBJECT TO CONFIRMATION AND CO-ORDINATION WITH ARCHITECTS DRAWINGS AND SPECIALISTS LINE LOADS


P1	DM	Preliminary - Costing	00.00.00
CD	DR	AMENDMENTS	DATE

STATUS: **PRELIMINARY**

**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical. Tel: 0121 781 7379  
Insulslab Sales. Tel: 0844 5766 726  
e-mail: [insulslab@ghwconsulting.co.uk](mailto:insulslab@ghwconsulting.co.uk) e-mail: [sales@insulslab.com](mailto:sales@insulslab.com)

[www.insulslab.com](http://www.insulslab.com)



**Foundation Plan**  
(HouseType Example)  
S.O.P. Denotes 'Setting Out Point' of Pod Units

**NOTE:**  
Where ground levels have been raised / adjusted, it is assumed that a suitable engineered material has been laid and consolidated in order to achieve a minimum ground bearing pressure 50kN/m<sup>2</sup>

- Hatched areas denotes pour one of two stage pour - see plan & sections
- Hatched areas denote insulslab pods cut on site to suit.

**THIS DRAWING IS FOR COSTING PURPOSES ONLY AND MUST NOT BE USED FOR CONSTRUCTION**

FOR CONSTRUCTION DETAIL INFORMATION CONTACT GHW CONSULTING ENGINEERS LTD.

CLIENT

CONTACT: **New Development** 12-2999

TITLE: **Insulslab Foundation Layout Example Housetype**

DRAWN	DM	CREATED	AW	APPROVED	AW
SCALE	A1 - 1:25 A3 - 1:50	DATE	Nov 2012		

JOB NO. **INS12-0000** DRAWING NO. **01** REVISION **P1**

To be confirmed.  
Extent of any underbuild  
Gas regime

Gas membrane TBC  
Gas Venting TBC

**Insulslab SFRC Foundation Installation Methodology.**

Described below is a method of construction to utilise the INSULSLAB form of waffle slab foundation in conditions where the foundation is supported at shallow depth directly by the underlying soils. For piled foundations using INSULSLAB similar methods apply.  
Whilst accepting that individual interpretation and innovation may well give rise to alternative methods to suit site specific conditions, it is felt that what is described, will clearly and accurately achieve the end product.  
Severely sloping sites will introduce individual conditions to be addressed which can be readily accounted for by referring to Insulslab technical, however for the purposes of this exercise we have assumed a relatively level site.

THIS DRAWING IS COPYRIGHT AND MUST NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT PRIOR PERMISSION.  
© 2012. GHW CONSULTING ENGINEERS LTD. / INSULSLAB SIG

**General Notes.**

1. Insulslab foundation to be placed on minimum 150mm Type 2 granular material to be compacted in accordance with the specification.
2. All works to be undertaken in accordance with the recommendations contained within the geotechnical report and NHBC Standards. Where trees are present, ground conditions may require the placing of an additional hardcore bed under the whole area to overcome the influence of trees/rottable soils in accordance with the NHBC Standards Chapter 4.2 and 4.5.
3. For depths of sub-base required beneath edge beams refer to sections.
4. The Insulslab pods have a load bearing requirement and are protected by a patent. Online technical data and ordering information can be found on the website [www.insulslab.com](http://www.insulslab.com).
5. Slab to be cured under a spray application of curing / sealing solution, Permaban Pro-Seal or similar.
6. Where ground levels have been adjusted to suit site set-out requirements, it has been assumed that infill / regrade material has been suitably engineered and consolidated in order to achieve a minimum ground bearing capacity of 50kN/m<sup>2</sup>.
7. For all general details and sections see drawing No. 100.
8. For on site setting out of units, orientation / handling and co-ordination, see Architects detail drawings and relevant site setting out drawings by others.
9. For all finished ground levels and slab levels, see Architects / Set-out drawings by others.
10. For setting out of all services, drainage and utilities see Architects and specialists detail drawings.

**Specification for Concrete and Fibres.**

1. The concrete mix shall follow the recommendations as noted in the ArcolorMittal Sheffield Ltd. BBA Certification 12 / 4894 product sheet 2 "ArcolorMittal - Insulslab foundation system for housing applications using SFRC" page 3, Table 1 Concrete Specifications along with the following mix design guide lines. These are to be considered together and neither is to be considered complete without the other.
2. Concrete mix design shall be based on the use of 20mm aggregate. Other aggregate sizes or blends may be used on further review by ArcolorMittal in conjunction with the readymix supplier and only formal written confirmation from ArcolorMittal. The proportions will depend on the gradation of the local materials.
3. The concrete grade to be a C30 / 37 - C35 with a maximum water cement ratio of 0.55 using super-plasticiser. All admixtures used should be from the same manufacturer and used as per manufacturers instructions.
4. Permitted cement type shall be Portland cement or blends of up to 20% replacement using GGBS or PFA. This corresponds to the following cement types to BS EN 197-1: CEM I, CEM III/A-S OR CEM III/A-V. Minimum cement quantity to be 320kg/m<sup>3</sup>.
5. The slump shall be between 180 and 230mm (S4 type EN206 / BS8600) at the time of delivery. The addition of water on site is prohibited, except where the additional water is allowable water remaining from the original batch target. Any water added to the concrete shall be recorded on the delivery ticket.
6. The fines content shall be approximately 50% by weight of the total aggregate content. Total fines content shall be <math>450\text{kg/m}^3</math> fines graded at or below 200µ. Please refer to the required sieve curve analysis for optimum aggregate gradation to be used when investigating the suitability of the given mix.
7. Steel fibres to be HE-1/50. Dosage rate is 50 kg/m<sup>3</sup>.

**NOTE:**  
LAYOUT SHOWN IS INDICATIVE AND SUBJECT TO CONFIRMATION AND CO-ORDINATION WITH ARCHITECTS DRAWINGS AND SPECIALISTS

REV	DATE	DESCRIPTION
P1	DM	Preliminary - Costing
00.00.00		
AMENDMENTS		DATE

STATUS: **PRELIMINARY**

**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
Insulslab Sales: Tel: 0844 5766 726  
Email: [insulslab@ghwconsulting.co.uk](mailto:insulslab@ghwconsulting.co.uk) Email: [sales@insulslab.com](mailto:sales@insulslab.com)

[www.insulslab.com](http://www.insulslab.com)


CLIENT

CONTRACT: **New Development** 12-2999

TITLE: **Insulslab Foundation Layout Example Housetype**

DRAWN	DM	CHECKED	AW	APPROVED	AW
SCALE	A1 - 1:25 A3 - 1:50	DATE	Nov 2012		


JOB NO. **INS12-0000** DRAWING NO. **01** REVISION **P1**



**Foundation Plan**

(HouseType Example)

● S.O.P. Denotes 'Setting Out Point' of Pod Units



Max Pile Load = 360kN

See drawing /51 for reinforcement details

- Hatched areas denotes pour one of two stage pour - see plan & sections
- Hatched areas denote insulslab pods cut on site to suit.

**THIS DRAWING IS FOR COSTING PURPOSES ONLY AND MUST NOT BE USED FOR CONSTRUCTION**

FOR CONSTRUCTION DETAIL INFORMATION CONTACT GHW CONSULTING ENGINEERS LTD.

**NOTE:**  
Where ground levels have been raised / adjusted, it is assumed that a suitable engineered material has been laid and consolidated in order to achieve a minimum ground bearing pressure 50kN/m<sup>2</sup>

**General Notes.**

1. For notes refer to drg /01

**REINFORCED CONCRETE NOTES**

1. FOR CONCRETE NOTES REFER TO GA DRAWING.

2. CONCRETE COVER:  
 GROUND BEAMS - 30 TOP, SIDES AS SHOWN, 75 BTM

COVER TO REINFORCEMENT IS TO BE ACHIEVED AND MAINTAINED BY USE OF PROPRIETARY ACCESSORIES IN ACCORDANCE WITH BS 7973.

5. WHERE APPLICABLE, REBAR LAP LENGTHS ARE NOT TO BE LESS THAN 40 x BAR DIA. WHERE ONE BAR LAPPS WITH ANOTHER OF A DIFFERENT DIAMETER, THEN USE THE LAP LENGTH FOR THE SMALLER BAR. PREWELDED MESH LAP LENGTHS ARE TO BE NOT LESS THAN 400mm.

6. CONCRETE SURFACE FINISHES ARE TO BE IN ACCORDANCE WITH THE SPECIFICATION.

7. LAYER ABBREVIATIONS (WHERE USED)

- BTM - BOTTOM FACE
- TOP - TOP FACE
- B1 - OUTERMOST LAYER IN BTM
- B2 - SUBSEQUENT LAYER IN BTM
- T1 - OUTERMOST LAYER IN TOP
- T2 - SUBSEQUENT LAYER IN TOP
- N1 - OUTERMOST LAYER IN NEAR FACE
- N2 - SUBSEQUENT LAYER IN NEAR FACE
- F1 - OUTERMOST LAYER IN FAR FACE
- F2 - SUBSEQUENT LAYER IN FAR FACE
- EF - EACH FACE
- EW - EACH WAY
- STG - STAGGERED
- ABR - ALTERNATE BARS REVERSED

8. REBARS TO BE PRE-FIXED BY THE DRAWING NUMBER.

09. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH GHW Drg. No. 01, IN ADDITION TO OTHER DRAWINGS REFERENCED THEREIN.


10. REINFORCEMENT NOMENCLATURE:

5H40-01-150-T1 ABR	COMMENT
L	LOCATION OF BARS
C	BAR CENTRES (mm)
M	BAR MARK
D	BAR DIAMETER (mm)
T	TYPE OF STEEL
N	NUMBER OF BARS

**NOTE:**  
 LAYOUT SHOWN IS INDICATIVE AND SUBJECT TO CONFIRMATION AND CO-ORDINATION WITH ARCHITECTS DRAWINGS AND SPECIALISTS LINE LOADS

REV	DATE	DESCRIPTION
P1	DM	Preliminary - Costing
02	DM	AMENDMENTS
03	DM	AMENDMENTS

STATUS: **PRELIMINARY**



**INSULSLAB SFRC**  
 HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: 0121 781 7379  
 Insulslab Sales: 0844 5766 726  
 e-mail: insulslab@ghwconsulting.co.uk | e-mail: sales@insulslab.com




www.insulslab.com

CLIENT:   
 CONTRACT: **New Development** 12-2999

TITLE: **Reinforcement details for Example Housetype**

DRAWN	DM	CREATED	AW	APPROVED	AW
SCALE	A1 - 1:25	DATE	Nov 2012		
	A3 - 1:50				

JOB NO. **INS12-0000** DRAWING NO. **51** REVISION **P1**




**NOTE:**  
 Where ground levels have been raised / adjusted, it is assumed that a suitable engineered material has been laid and consolidated in order to achieve a minimum ground bearing pressure 50kN/m<sup>2</sup>





**THIS DRAWING IS FOR COSTING PURPOSES ONLY AND MUST NOT BE USED FOR CONSTRUCTION**

FOR CONSTRUCTION DETAIL INFORMATION CONTACT GHW CONSULTING ENGINEERS LTD.





**TYPICAL EDGE DETAIL AT SERVICE ENTRY POINTS  
(SECTION 1)**

 HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS



**DPM DETAIL (WHERE GAS MEMBRANE REFER TO PLOT SPECIFIC DRGS)**

<b>TYPICAL EDGE DETAIL</b>		 <b>INSULSLAB SFRC</b> HIGH QUALITY FOUNDATION SYSTEM
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>200</b>	REVISION <b>P1</b>
Insulslab Technical. Tel: 0121 781 7379 e-mail: insulslab@ghwconsulting.co.uk		Insulslab Sales. Tel: 0844 5766 726 e-mail: sales@insulslab.com <a href="http://www.insulslab.com">www.insulslab.com</a>



**TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM  
(SECTION 3 - ALSO REFER TO /102)**



HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS

**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM


Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com

www.insulslab.com

**TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM/UNDERBUILD**

JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>202</b>	<b>P1</b>



**TYPICAL DETAIL AT INTERNAL/PARTY WALLS**  
**(SECTION 5)**



HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS

**INSULSLAB SFRC**  
 HIGH QUALITY FOUNDATION SYSTEM


Insulslab Technical: Tel: 0121 781 7379  
 e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
 e-mail: sales@insulslab.com


www.insulslab.com


**TYPICAL DETAIL AT  
 INTERNAL/PARTY LOAD  
 BEARING WALLS**

JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>203</b>	<b>P1</b>



**TYPICAL DETAIL AT CHANGE IN  
SLAB LEVEL AT PARTY WALLS  
(SECTION 6)**

 HATCHED AREAS  
DENOTES POUR ONE  
OF TWO STAGE POUR -  
SEE PLAN & SECTIONS




**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM


Insulslab Technical.      Insulslab Sales.  
Tel: 0121 781 7379      Tel: 0844 5766 726  
e-mail: insulslab@ghwconsulting.co.uk      e-mail: sales@insulslab.com  
www.insulslab.com

<b>CHANGE IN SLAB LEVEL AT PARTY WALL BEAMS</b>		
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>204</b>	REVISION <b>P1</b>





**TYPICAL DETAIL AT CHANGE IN SLAB  
LEVEL TO GARAGE - 150 STEP MAX  
(SECTION 7)**



HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS

**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com



www.insulslab.com


**TYPICAL CHANGE IN  
SLAB LEVEL ADJACENT  
GARAGE**


JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>205</b>	<b>P1</b>



VIBRO TO BE INSTALLED TO 100kN/m<sup>2</sup> UNDER EXTERNAL AND INTERNAL BEAMS ONLY. SLAB IS DESIGNED TO SPAN BETWEEN BEAMS.



 HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS



**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM


Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com


www.insulslab.com


**TYPICAL EDGE DETAIL FOR VIBRO OR ENGINEERED FILL SITES**


JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>210</b>	<b>P1</b>




**TYPICAL EDGE DETAIL AT SERVICE ENTRY POINTS  
(SECTION 1)**


 HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS



<b>TYPICAL EDGE DETAIL</b>		 <b>INSULSLAB SFRC</b> <small>HIGH QUALITY FOUNDATION SYSTEM</small>
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>220</b>	REVISION <b>P1</b>
<small>Insulslab Technical. Tel: 0121 781 7379 email: insulslab@ghwconsulting.co.uk</small>		<small>Insulslab Sales. Tel: 0844 5766 726 email: sales@insulslab.com</small> <a href="http://www.insulslab.com">www.insulslab.com</a>



**TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM  
(SECTION 3 - ALSO REFER /103)**



HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS


**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk


Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com

www.insulslab.com

<b>TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM/UNDERBUILD</b>		
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>222</b>	REVISION <b>P1</b>



**TYPICAL DETAIL AT INTERNAL/PARTY WALLS**  
**(SECTION 5)**



HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS




Insulslab Technical: Tel: 0121 781 7379  
 Insulslab Sales: Tel: 0844 5766 726  
 e-mail: insulslab@ghwconsulting.co.uk e-mail: sales@insulslab.com  
 www.insulslab.com

**TYPICAL DETAIL AT  
 INTERNAL/PARTY LOAD  
 BEARING WALLS**


JOB NO.  
**INS 12-0**


DRAWING NO.  
**223**

REVISION  
**P1**



**TYPICAL DETAIL AT CHANGE IN  
SLAB LEVEL AT PARTY WALLS  
(SECTION 6)**

 HATCHED AREAS  
DENOTES POUR ONE  
OF TWO STAGE POUR -  
SEE PLAN & SECTIONS



**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com


www.insulslab.com

**CHANGE IN SLAB LEVEL  
AT PARTY WALL BEAMS**


JOB NO.  
**INS 12-0**


DRAWING NO.  
**224**

REVISION  
**P1**



**TYPICAL DETAIL AT CHANGE IN SLAB LEVEL TO GARAGE - 150 STEP MAX (SECTION 7)**

 HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS





**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com

www.insulslab.com

<b>TYPICAL CHANGE IN SLAB LEVEL ADJACENT GARAGE</b>		
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>225</b>	REVISION <b>P1</b>



**DETAIL BETWEEN POURS**

1. INSTALL TEMPORARY FORMWORK
2. BACKFILL WITH GEN0 LEAN MIX
3. CAST POUR 1 IN SFRC
4. CAST POUR 2 IN SFRC
5. CAST MAIN SLAB IN SFRC

HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS



**TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM  
OPTION 1**

**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
 Insulslab Sales: Tel: 0844 5766 726  
 e-mail: insulslab@ghwconsulting.co.uk e-mail: sales@insulslab.com  
 www.insulslab.com


<b>TYPICAL RAFT DETAILS AT UNDERBUILD</b>		
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>240</b>	REVISION <b>P1</b>






**DETAIL BETWEEN POURS**

1. CAST POUR 1 IN SFRC
2. BUILD BLOCKWORK OR SIMILAR SUIT POUR 2 HEIGHT AND INSTALL INSULATION
3. BACKFILL WITH SUITABLE WELL COMPACTED FILL
4. CAST POUR 2 IN SFRC
5. CAST MAIN SLAB IN SFRC

 HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS

**TYPICAL EDGE DETAIL AT DEEPEDED EDGE BEAM  
OPTION 2**



**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM



Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com

www.insulslab.com

**TYPICAL RAFT DETAILS  
AT UNDERBUILD  
OPTION 2**

JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>241</b>	<b>P1</b>



**DETAIL BETWEEN POURS**

1. INSTALL TEMPORARY FORMWORK
2. BACKFILL WITH GEN0 LEAN MIX
3. CAST POUR 1 IN SFRC
4. CAST POUR 2 IN SFRC
5. CAST MAIN SLAB IN SFRC

HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS



**TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM  
OPTION 1**



INSULSLAB Technical, Tel: 0121 781 7379, e-mail: insulslab@ghwconsulting.co.uk  
INSULSLAB Sales, Tel: 0844 5766 726, e-mail: sales@insulslab.com  
www.insulslab.com


**TYPICAL PILE DETAILS  
AT UNDERBUILD  
OPTION 1**

JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>242</b>	<b>P1</b>




**DETAIL BETWEEN POURS**

1. CAST POUR 1 IN SFRC
2. BUILD BLOCKWORK OR SIMILAR TO SUIT POUR 2 HEIGHT AND INSTALL INSULATION
3. BACKFILL WITH SUITABLE WELL COMPACTED FILL
4. CAST POUR 2 IN SFRC
5. CAST MAIN SLAB IN SFRC

 HATCHED AREAS DENOTES POUR ONE OF TWO STAGE POUR - SEE PLAN & SECTIONS




**TYPICAL EDGE DETAIL AT DEEPENED EDGE BEAM  
OPTION 2**



**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical, Tel: 0121 781 7379, e-mail: insulslab@ghwconsulting.co.uk  
Insulslab Sales, Tel: 0844 5766 726, e-mail: sales@insulslab.com  
www.insulslab.com

<b>TYPICAL PILE DETAILS AT UNDERBUILD OPTION 2</b>		
JOB NO. <b>INS 12-0</b>	DRAWING NO. <b>243</b>	REVISION <b>P1</b>



**INSULSLAB SFRC**  
HIGH QUALITY FOUNDATION SYSTEM

Insulslab Technical: Tel: 0121 781 7379  
e-mail: insulslab@ghwconsulting.co.uk

Insulslab Sales: Tel: 0844 5766 726  
e-mail: sales@insulslab.com

www.insulslab.com

**TYPICAL DETAIL OF VOID FORMER UNDER INSULSLAB PILED FOUNDATION**

JOB NO.	DRAWING NO.	REVISION
<b>INS 12-0</b>	<b>244</b>	<b>P1</b>